


SAMOD

STAND ALONE MODULATING DAMPER CONTROL



ZONEX SAMOD		
THERMOSTAT	T-1	SAMOD
TRANSFORMER	TR-1	SYSTEM POWER 24 V- 40 VA
LAT SENSOR	TS-1	DUCT TEMPERATURE SENSOR
TERMINAL CONNECTIONS		
SAMOD CONTROLLER AND ACTUATOR		
TR-1	24 VAC POWER INPUT	
TR-2	24 VAC POWER COMMON	
RO	DAMPER RUN OPEN SIGNAL	
RC	DAMPER RUN CLOSED SIGNAL	
MC	24 VAC MOTOR COMMON	
DS	DUCT TEMPERATURE SENSOR	
AUX	OPTIONAL AUXILIARY HEAT	
C	AUXILIARY HEAT COMMON	

NOTES: PROVIDE MODULATING ZONEX ROUND OR RECTANGULAR DAMPER OR D-FUSER DESIGNED TO SUPPORT UP TO 1.75" S.P.

AUX CONTACTS USED TO CONTROL SUPPLEMENTAL HEAT SOURCE: I.E. BASEBOARD OR RADIANT PANEL IF ELECTRIC HEAT IS USED AN AIR PROVING SWITCH MUST BE INSTALLED

VISIT OUR ON-LINE CATALOG AT ZONEXPRODUCTS.COM
 FOR APPLICATIONS ASSISTANCE CALL 800-228-2966