

COMPONENT SELECTION GUIDE

GEN V Control Solutions

Manage the entire system from one central HUB

Part # - GEN V

1 - Per RTU or Split System

Supports 2 - 20 Fully Modulating Zones or Standalone Units

Daisy Chain: Zonex communication wire Part#-3TWP and 24VAC from Thermostat to Thermostat
Only 1-24VAC / 100VA Transformer Powers the GEN V and up to 20 modulating dampers

HUB - Touch Screen Thermostat

Part # - EzTouchV

Need 1 Hub Thermostat per GEN V system

Slave Up to 3 Zone Dampers per Stat

Zone Touch Screen Thermostat

Part # - EzTouchX

1- Thermostat per Damper

Slave Up to 3 Zone Dampers per Stat

Modulating Zone Dampers

Part #

STMPD + Damper Size - Round Damper (up to 1.75 S.P.)

STCD + Damper Size - Rectangular Dampers (up to 1.75 S.P.)

Electronic Bypass Damper

(Includes Integrated Static Pressure Control)

Part #

STBP + Damper Size - Round Bypass Dampers

STCDBP + Damper Size - Rectangular Bypass Dampers

1-24vac / 40va Transformer to Power Bypass Damper

Optional - Wireless Temperature Access Point

Part # - TAP

1- TAP per Damper

Mount anywhere and communicate wirelessly to its damper

Thermostat to Control Standalone Units

Part # - SATouchX

Controls and Networks Standalone RTU or Split systems
with SA / RA / RH reporting

THIS COMPLETES YOUR GEN V SYSTEM

For assistance, contact Zonex at (800) 228-2966
or visit zonexproducts.com for more information

