

COMPONENT SELECTION GUIDE

GEN V Control Solutions

Manage the entire system from one central HUB

Part # - GEN V

1 - Per RTU or Split System

Supports 2 - 10 Power closed / Spring open dampers

Daisy Chain: Zonex communication wire Part#-3TWP and 24VAC from Thermostat to Thermostat
Only 1-24VAC / 100VA Transformer Powers the GEN V and up to 10 PC/SO dampers

HUB - Touch Screen Thermostat

Part # - EzTouchV

Need 1 Hub Thermostat per GEN V system

Slave Up to 3 Zone Dampers per Stat

Zone Touch Screen Thermostat

Part # - EzTouchX

1- Thermostat per Damper

Slave Up to 3 Zone Dampers per Stat

Low Pressure Zone Dampers

Part #

TR + Damper Size - Round Damper (up to .5" S.P.)

TREC + Damper Size - Rectangular Dampers (up to .5" S.P.)

Bypass Damper

Part #

101ABBD + Damper Size - Round Bypass Dampers

RBB + Damper Size - Rectangular Bypass Dampers

Optional - Wireless Temperature Access Point

Part # - TAP

1- TAP per Damper

Mount anywhere and communicate wirelessly to its damper

Thermostat to Control Standalone Units

Part # - SATouchX

Controls and Networks Standalone RTU or Split systems
with SA / RA / RH reporting

THIS COMPLETES YOUR GEN V SYSTEM

For assistance, contact Zonex at (800) 228-2966
or visit zonexproducts.com for more information

