

COMPONENT SELECTION GUIDE

GEN X

Wi-Fi APP Based Controller

Part # - GEN X

Includes Mobile APP

1 - Per RTU or Split System

Supports 2 - 20 Fully Modulating Zones

Add Part # **GEN X-RM** to expand your GEN-X system by adding a GEN X-RM controller for each additional unit
(Each GEN X-RM supports 2-20 fully modulating Zones)

Daisy Chain: Zonex communication wire Part#-3TWP and 24VAC from Damper to Damper

Only 1-24VAC / 40VA Transformer Powers the GEN X and up to 20 modulating dampers

Each GEN X-RM expansion controller requires an additional transformer to support up to 20 dampers per GEN X-RM

Wireless Thermostat

Part # - WSTATX

1-Thermostat per Damper

Slave Up to 3 Zone Dampers per Thermostat



Wired Thermostat to Control Standalone Units

Part # - SASAT

Controls and Networks Standalone RTU or Split systems
with SA / RA reporting from the mobile app

Modulating Zone Dampers

Part #

WSTX + Damper Size - Round Damper (up to 1.75 S.P.)

WCDX + Damper Size - Rectangular Dampers (up to 1.75 S.P.)

Electronic Bypass Damper

(Includes Integrated Static Pressure Control)

Part #

STBP + Damper Size - Round Bypass Dampers

STCDBP + Damper Size - Rectangular Bypass Dampers

1-24vac / 40va Transformer to Power Bypass Damper

RLYX

Part # - RLYX

Control and Schedule up to 5 Generic Loads

THIS COMPLETES YOUR GEN X SYSTEM

For assistance, contact Zonex at (800) 228-2966
or visit zonexproducts.com for more information

