

GEN X-RETROZONE

COMPONENT SELECTION GUIDE

GEN X

Wi-Fi APP Based Controller

Part # - GEN X

Includes Apple or Android Mobile APP and Access from any Web Browser

1-Per RTU or Split System

Supports 2 – 20 Fully Modulating Zones

Add Part# **GEN X-RM** to expand your GEN X system by adding a GEN X-RM controller for each additional zoned unit.
(Each GEN X-RM supports 2-20 fully modulating Zones or thermostats)

Daisy Chain: Zonex communications wire and 24VAC from Stat to Stat

1-24VAC / 100VA Transformer Powers the *GEN X* and All the Dampers in the System

Each GEN X-RM expansion controller requires an additional transformer to support up to 20 dampers per GEN X-RM

Color Touch Screen Thermostat with Actuator

Part # - RZKITX

1-Thermostat (EzTouchX) and Actuator (101AHDM) per Damper

Slave Up to 3 Zone Dampers per Stat

Modulating Zone Dampers

Part #

STMPD + Damper Size -Round Dampers (up to 1.75 S.P)

STCD + Damper Size -Rectangular Dampers (up to 1.75 S.P)

Color Touch Screen Thermostat to Control Standalone Units

Part # - SATouchX

Controls and Networks Standalone RTU or Split systems

With SA / RA / RH reporting from the mobile app

Electronic By-Pass Damper

Part #

STBP + Damper Size -----Round By-Pass Dampers

STCDBP + Damper Size ----- Rectangular By-Pass Dampers

(Includes Integrated Static Pressure Control)

1-24VAC / 40VA Transformer to Power By-Pass Damper

RLYX

Part # - RLYX

Control and Schedule up to 5 Generic Loads

THIS COMPLETES YOUR GEN X SYSTEM USING WIRED THERMOSTATS